

BATTERY POWERED

Compaction
Equipment




100%
EMISSION
FREE

weberm

We Know Compaction

ENGINEERED AND BUILD BY THE SPECIALIST OF HAND-GUIDED COMPACTION EQUIPMENT.

Weber MT offers new opportunities for emission sensitive and restricted areas: Machines with Battery and DC-engine technology.

This makes it possible to work in closed rooms, deeper trenches, and in emission-regulated cities.

The base for our newly developed, battery-powered machines are the associated models with gasoline engines. In terms of performance and work results, vibratory plates, reversible plates, vibratory rammers, and paver rollers with batteries are in no way inferior to comparable gasoline machines.

TYPE	SRE 590 DC	CF 2 DC	CF 3 DC	CFR 90 DC	CR 2 DC	VPR 700 DC
Operating weight (incl. battery)	68 kg	87 kg	102 kg	96 kg	143 kg	183 kg
Operating weight (without battery)	62 kg	81 kg	96 kg	90 kg	137 kg	177 kg
Working width	28 cm	45 cm	50 cm	43 cm	45 cm	67 cm
Centrifugal force / Stroke force	17.5 kN	15 kN	20 kN	14 kN	20 kN	14 kN
Engine output	Honda GXE 2.0 / 1.8 kW	Honda GXE 2.0 / 1.8 kW	Honda GXE 2.0 / 1.8 kW	Honda GXE 2.0 / 1.8 kW	Honda GXE 2.0 / 1.8 kW	Honda GXE 2.0 / 1.8 kW
Operating speed	3,000 / 3,300 / 3,600 1/min.	3,600 1/min.	3,600 1/min.	3,600 1/min.	3,600 1/min.	3,600 1/min.
Working speed	21 m/min.	26 m/min.	24 m/min.	26 m/min.	21 m/min.	Machine is advanced by the operator
Dimensions (LxWxH)	74 x 35 x 111 cm	113 x 45 x 96 cm	113 x 50 x 96 cm	46 x 43 x 98 cm	122 x 45 x 95 cm	125 x 72 x 95 cm

ADVANTAGES

- Modular design**
 One battery fits all machines of the new Weber MT DC-Line. Tool free and easy change of the Battery.
- Clearly arranged**
 Direct feedback about state of charge on each battery, as well as self-diagnostic with fault indication. Intuitive and self-explanatory operating of the engine.
- Reliable**
 Combination of Battery and DC-Engine are especially designed for small construction machines.
- Less maintenance**
 Battery and engine requires less maintenance compared to conventional gasoline engines.
- Easy to operate**
 Simple and convenient push button Start/Stop of the engine.
- Eco-Friendly**
 No direct CO₂ -emission, no petrol fumes, no contamination of soil or paved surfaces with gasoline.

TYPE	BATTERY LI-ION
Weight	6.4 kg
Energy content	720 Wh
Rated voltage	72 V
Rated capacity	10 Ah
Charging time 0 - 80 %	1 hour
Charging time 0 - 100 %	1.5 hours

TYPE	BATTERY CHARGER HONDA
Weight	11 kg
Power connection	230 V, 50 Hz, max. 10 A



Accessories as with comparable gasoline machines.





Weber Maschinenteknik GmbH

Im Boden 5-8, 10 · 57334 Bad Laasphe · Germany

Phone +49 2754 398 0 · Fax +49 2754 398 101

info@webermt.de · www.webermt.de



WeberMT



webermtofficial



MyWeberMT